

LD3811 / LD381T

Monomeric Digital Print Vinyl

Protective Laminate LP3812, LP3842, LP40000 / LP41000



Dated: 7.2012

LD3811 / LD381T

Monomeric Digital Print Vinyl

Type	LD3811	LD381T
Production	Piezo Ink Jet	
Application Period	Medium term applications	
Areas of Use	Indoor and outdoor advertising, flat and even surfaces for exhibition booths or other promotions.	
Colors	White glossy, white matt	
Adhesive	Pressure sensitive, grey pigmented, acrylic based.	
Application Characteristics		Airfree™ technology allows trapped air to be released during application, making it easier to remove trapped bubbles and increase overall efficiency and productivity.
ICC Profiles	Seiko: Colorpainter Roland: VersaCamm/SolJet Pro II Mutoh: Value Jet/Toucan LT/Falcon/Falcon II Mimaki: JV3 HP: 9000 Download ICC profiles under: http://sign.lghausys.eu/en/ld3811 We constantly update our available ICC profiles. Should you have further questions please visit our website.	
Film Coat	PVC	
Production Process	Monomeric calendered	
Thickness	0.10 mm	
Service Temperature Range	-45 °C – +82 °C	
Application Temperature	Minimum +10 °C	
Durability	4 years	
Removability	Permanent	
Protective Laminate	LP3812, LP3842, LP40000/LP41000	

